



Job Name: \_\_\_\_\_

Job Location: \_\_\_\_\_

Contractor: \_\_\_\_\_

Engineer: \_\_\_\_\_

Approval: \_\_\_\_\_

## Con-Stab® Elbows - 90°

### Design Features:

- Continental's patented "ID Seal"
- For underground PE pipe (ASTM D 2513) only
- Made in USA


### Operating Specifications:

Temperature: -20° to 140° F  
 Pressure: 125 psi



Always Match Pipe Size & SDR

You must use a Continental Chamfer Tool on a Continental Fitting



Continental Industries is an ISO 9001 Certified Company.  
 NFPA 58, LP-Gas Code                      NFPA 54, National Fuel Gas Code  
 ICC – International Plumbing Code      IAPMO – Uniform Plumbing Code  
 Approved by the Commonwealth of Massachusetts  
 D.O.T., Title 49 of the Code of Federal Regulations, Part 192.283 (b)  
 ASME B31.8-1995 "Gas Transmission and Distribution Piping Systems"  
 ASTM D 2513 "Standard Specification for Thermoplastic Gas Pressure Pipe, Tubing and Fittings"



WR#	Size	Wall Thickness	Overall Length	Weight (lbs.)	Required Chamfer Tool
2882000	1/2" CTS	.090 Wall	3-1/2"	0.43	2888020
2882002	3/4" IPS	SDR-11	4-1/4"	0.80	2888014
2882004	1" IPS	SDR-11	4-1/2"	1.10	2888016
2882020	1" CTS	.099/.101 Wall	4-1/4"	0.79	2888022
2882006	1-1/4" IPS	<b>SDR-10</b>	9-1/4"	2.10	2888006
2882007	1-1/4" IPS	SDR-11	9-1/2"	2.10	2888007
2882008	1-1/2" IPS	SDR-11	9-7/8"	3.00	2888008
2882010	2" IPS	SDR-11	10-3/8"	3.65	2888010