



Job Name: _____

Job Location: _____

Contractor: _____

Engineer: _____

Approval: _____

Con-Stab® Tees

Design Features:

- Continental's patented "ID Seal"
- For underground PE pipe (ASTM D 2513) only
- Made in USA

Operating Specifications:

Temperature: -20° to 140° F
 Pressure: 125 psi



Always Match Pipe Size & SDR

You must use a Continental Chamfer Tool on a Continental Fitting



Continental Industries is an ISO 9001 Certified Company.
 NFPA 58, LP-Gas Code NFPA 54, National Fuel Gas Code
 ICC – International Plumbing Code IAPMO – Uniform Plumbing Code
 Approved by the Commonwealth of Massachusetts
 D.O.T., Title 49 of the Code of Federal Regulations, Part 192.283 (b)



ASME B31.8-1995 "Gas Transmission and Distribution Piping Systems"
 ASTM D 2513 "Standard Specification for Thermoplastic Gas Pressure Pipe, Tubing and Fittings"



WR#	Size	Wall Thickness	Overall Length	Height	Weight (lbs.)	Required Chamfer Tool
2883000	1/2" CTS	.090 Wall	5-1/2"	2-15/16"	0.6	2888020
2883002	3/4" IPS	SDR-11	6"	3-1/16"	1.0	2888014
2883004	1" IPS	SDR-11	6-1/4"	3-1/4"	1.5	2888016
2883020	1" CTS	.099/.101 Wall	6"	3-1/16"	1.3	2888022
2883006	1-1/4" IPS	SDR-10	17-1/2"	8-13/16"	3.0	2888006
2883007	1-1/4" IPS	SDR-11	17-1/2"	8-13/16"	3.0	2888007
2883008	1-1/2" IPS	SDR-11	17-3/8"	8-3/4"	4.6	2888008
2883010	2" IPS	SDR-11	18-3/4"	9-3/8"	5.5	2888010