



Job Name: _____

Job Location: _____

Contractor: _____

Engineer: _____

Approval: _____

Stainless Steel Gas Range Connector

Design Features:

- Corrosion, UV, and Salt Resistant Epoxy Coating
- One Piece Construction
- Out Performs Industry Standards for Torsion (1.5X) and Repeated Bending (2X)
- 100% Leak Tested
- Domestic



Use: For use with indoor and outdoor connections of gas appliances to gas piping system. May be used with natural, manufactured, mixed and liquefied petroleum (LP or Propane) gasses and LP gas-air mixtures.

Operating Specifications:

Temperature: -40° to 150° F

Pressure: Standard Line Pressures up to 1/2 psi Max

Material Specifications	
Part	Material
Tubing	Stainless Steel - 304
Coating	Yellow Polymer Blend
Nuts	Brass - C36000
Fittings	Brass - C36000



CSA listed to ANSI Z21.24 / CSA 6.10 Standard "Connectors for Gas Appliances"
 CSA listed to ANSI Z21.75 / CSA 6.27 Standard "Connectors for Outdoor Appliances & Manufactured In The Commonwealth of Massachusetts"

W-R#	Size	Length	BTU/hr (NG)	BTU/hr (LPG)	Watts/hr (NG)	Weight
0813004	1/2" ID (5/8" OD)	24"	150,000	240,000	43,961	.750 lbs.
0813008	1/2" ID (5/8" OD)	36"	125,000	200,000	36,634	.913 lbs.
0813012	1/2" ID (5/8" OD)	48"	106,000	169,600	31,066	1.06 lbs.
0813014	1/2" ID (5/8" OD)	60"	93,200	149,120	27,314	1.26 lbs.
0813016	1/2" ID (5/8" OD)	72"	86,000	137,600	25,380	1.36 lbs.