



Job Name: \_\_\_\_\_

Job Location: \_\_\_\_\_

Contractor: \_\_\_\_\_

Engineer: \_\_\_\_\_

Approval: \_\_\_\_\_

## Wax Floor Mounted Toilet Bowl Gaskets

### Design Features:

- Will Not Dry Out or Deteriorate
- Forms a Watertight, Gas Tight and Odor Tight Seal
- Ultra Hygenic: Will Not Support Bacteria
- Domestic

### Installation Instructions:

**Step 1:** Be sure gasket is at room temperature (~70° F)

**Step 2:** Place bowl upside down on a protective pad or blanket, place flange and gasket around discharge opening, extending plastic flange away from the bowl.

**Step 3:** Press gasket firmly into place to assure adhesion when bowl is inverted

**Step 4:** Carefully set toilet down on bolts and twist bowl slightly to spread wax and make a tight seal. Tighten bolts carefully to prevent breaking the bowl.

**1357002**  
Wax Gasket



**1358002**  
Deep with Horn



**1358202**  
Urethane Reinforced with Horn



Conforms to Federal Specification TT-P-1536A

W-R#	Description	OD	ID	Height	Weight	Box
1357002	Wax Gasket	5-1/2"	3-1/2"	1"	.393 lbs.	48
1358002	Deep with Horn	5-1/2"	2-1/2"	1-1/2"	.507 lbs.	24
1358202	Urethane Reinforced with Horn	5-1/2"	2-1/2"	1-7/8"	.495 lbs.	24