



Job Name: _____

Job Location: _____

Contractor: _____

Engineer: _____

Approval: _____

Wal-Rich Standard Pressure Gauges

Design Features:

- 1/4" NPT Brass Lower Connection
- Black Steel Case
- Imported

Use: For use with water, oil, and gas.
Not for use with oxygen.

Calibration: ANSI B40.1 Accuracy
Grade B-2% Mid Scale.



W-R#	Size	Range	Increments	Weight	W-R#	Size	Range	Increments	Weight
1712002	2"	0-15 psi	1/2 lb.	.230	1712802	3-1/2"	0-15 psi	1/2 lb.	.510
1712004	2"	0-30 psi	1/2 lb.	.230	1712804	3-1/2"	0-30 psi	1/2 lb.	.510
1712006	2"	0-60 psi	1 lb.	.230	1712806	3-1/2"	0-60 psi	1 lb.	.510
1712008	2"	0-100 psi	2 lb.	.230	1712808	3-1/2"	0-100 psi	2 lb.	.510
1712010	2"	0-160 psi	5 lb.	.230	1712810	3-1/2"	0-160 psi	5 lb.	.510
1712012	2"	0-200 psi	4 lb.	.230	1712812	3-1/2"	0-200 psi	4 lb.	.510
1712014	2"	0-300 psi	5 lb.	.230	1712814	3-1/2"	0-300 psi	5 lb.	.510
1712016	2"	0-400 psi	8 lb.	.230	1712816	3-1/2"	0-400 psi	8 lb.	.510
					1712818	3-1/2"	0-600 psi	10 lb.	.510
1712502	2-1/2"	0-15 psi	1/2 lb.	.295	1713002	4-1/2"	0-15 psi	1/2 lb.	.800
1712504	2-1/2"	0-30 psi	1/2 lb.	.295	1713004	4-1/2"	0-30 psi	1/2 lb.	.800
1712506	2-1/2"	0-60 psi	1 lb.	.295	1713006	4-1/2"	0-60 psi	1 lb.	.800
1712508	2-1/2"	0-100 psi	2 lb.	.295	1713008	4-1/2"	0-100 psi	2 lb.	.800
1712510	2-1/2"	0-160 psi	5 lb.	.295	1713010	4-1/2"	0-160 psi	5 lb.	.800
1712512	2-1/2"	0-200 psi	4 lb.	.295	1713012	4-1/2"	0-200 psi	4 lb.	.800
1712514	2-1/2"	0-300 psi	5 lb.	.295	1713014	4-1/2"	0-300 psi	5 lb.	.800
1712516	2-1/2"	0-400 psi	8 lb.	.295	1713016	4-1/2"	0-400 psi	8 lb.	.800
					1713018	4-1/2"	0-600 psi	10 lb.	.800

Warning: Misuse of this product may cause explosion and personal injury. Read ANSI-B40.1 and apparatus installation/operating instructions prior to use. DO NOT USE ON OXYGEN SERVICE.