



Job Name: \_\_\_\_\_

Job Location: \_\_\_\_\_

Contractor: \_\_\_\_\_

Engineer: \_\_\_\_\_

Approval: \_\_\_\_\_

# Stainless Steel Hose Clamps

### Design Features:

- Meets SAE J1508 Specification
- 1/2" Band
- 5/16" Slotted Hex Head Screw

### Operating Specifications:

- Screw Free Torque:** 4 in lbs. Max  
**Max Install Torque:** 20-25 in lbs.  
**Durability Torque:** 25 in lbs. Min



### Material Specifications

Part	Material
Band	Stainless Steel - 200
Housing	Stainless Steel - 200
<b>2208006 - 2208088:</b>	
Screw	Zinc Plated Carbon Steel
<b>2209006 - 2209040:</b>	
Screw	Stainless Steel - 400

W-R#	Weight	Screw Material	W-R#	Weight	Screw Material	SAE Size	Minimum Diameter	Maximum Diameter
2208006 (#6)	.0130 lbs.	ZP-Carbon	2209006 (#6)	.0395 lbs.	SS-400	#6	7/16"	25/32"
2208008 (#8)	.0140 lbs.	ZP-Carbon	2209008 (#8)	.0405 lbs.	SS-400	#8	1/2"	29/32"
2208010 (#10)	.0155 lbs.	ZP-Carbon	2209010 (#10)	.0430 lbs.	SS-400	#10	9/16"	1-1/16"
2208012 (#12)	.0155 lbs.	ZP-Carbon	2209012 (#12)	.0435 lbs.	SS-400	#12	11/16"	1-1/4"
2208016 (#16)	.0400 lbs.	ZP-Carbon	2209016 (#16)	.0460 lbs.	SS-400	#16	13/16"	1-1/2"
2208020 (#20)	.0415 lbs.	ZP-Carbon	2209020 (#20)	.0490 lbs.	SS-400	#20	13/16"	1-3/4"
2208024 (#24)	.0525 lbs.	ZP-Carbon	2209024 (#24)	.0525 lbs.	SS-400	#24	1-1/16"	2"
2208028 (#28)	.0555 lbs.	ZP-Carbon	2209028 (#28)	.0565 lbs.	SS-400	#28	1-5/16"	2-1/4"
2208032 (#32)	.0600 lbs.	ZP-Carbon	2209032 (#32)	.0595 lbs.	SS-400	#32	1-9/16"	2-1/2"
2208036 (#36)	.0635 lbs.	ZP-Carbon	2209036 (#36)	.0600 lbs.	SS-400	#36	1-13/16"	2-3/4"
2208040 (#40)	.0655 lbs.	ZP-Carbon	2209040 (#40)	.0620 lbs.	SS-400	#40	2-1/16"	3"
2208052 (#52)	.0675 lbs.	ZP-Carbon				#52	2-13/16"	3-3/4"
2208072 (#72)	.0725 lbs.	ZP-Carbon				#72	4-1/8"	5"
2208088 (#88)	.0800 lbs.	ZP-Carbon				#88	5-1/8"	6"