



Job Name: _____

Job Location: _____

Contractor: _____

Engineer: _____

Approval: _____

Natural Gas Quick-Connect Fittings

Design Features:

- Quick Disconnect

Operating Specifications:

Temperature: -40° to 250° F

Operating Pressure: 1/2 psi

Max. Flow Capacity: 60,000 BTU
@ .3 W.C. pressure drop

Use: For connecting low pressure outdoor gas appliances including BBQ grills, patio heaters, fire pits, crawfish burners, and beer brewers to a permanent gas supply line.

Female Quick Connect



Male Quick Connect



Quick Connect Adapter



ANSI Z21.41 Used for Natural & LP Gas

W-R#	Type	IP Size	Quick-Connection	Weight
2864002	Female QC	3/8" Female IPS	3/8" Female Quick-Connect	.246 lbs.
2864020	Female QC	1/2" Female IPS	1/2" Female Quick-Connect	
2864022	Female QC	3/4" Female IPS	3/4" Female Quick-Connect	
2846024	Female QC	1" Female IPS	1" Female Quick-Connect	
2864004	Male QC	3/8" Female IPS	3/8" Male Quick-Connect	.085 lbs.
2864040	Male QC	1/2" Female IPS	1/2" Male Quick-Connect	
2864042	Male QC	3/4" Female IPS	3/4" Male Quick-Connect	
2846044	Male QC	1" Female IPS	1" Male Quick-Connect	
2864006	QC Adapter	1/2" Male Flare	3/8" Male Quick-Connect	
2864008	QC Adapter	1/2" Female IPS	3/8" Male Quick-Connect	