



Job Name: _____

Job Location: _____

Contractor: _____

Engineer: _____

Approval: _____

Con-Stab® x Copper Flare - 45°

Design Features:

- Continental's Patented "ID Seal"
- For Underground PE Pipe (ASTM D 2513) C
- Made in the USA

Operating Specifications:

Temperature: -20° to 140° F
Pressure: 125 psi



Always Match Pipe Size & SDR



You must use a **Continental Chamfer Tool** on a **Continental Fitting**



Continental Industries is an ISO 9001 Certified Company.
 NFPA 58, LP-Gas Code
 NFPA 54, National Fuel Gas Code
 IAPMO - Uniform Plumbing Code
 ICC - International Plumbing Code



Approved by the Commonwealth of Massachusetts
 D.O.T., Title 49 of the Code of Federal Regulations, Part 192.283 (b)
 ASME B31.8-1995 "Gas Transmission and Distribution Piping Systems"
 ASTM D 2513 "Standard Specifications for Thermoplastic Gas Pressure Pipe, Tubing and Fittings"

W-R#	Size	SDR	Weight	Required Chamfer Tool
------	------	-----	--------	-----------------------

2884002	3/4" IPS x 1/2" CTS Flare	SDR-11	.655 lbs.	2888014
---------	---------------------------	--------	-----------	---------