



Job Name: \_\_\_\_\_

Job Location: \_\_\_\_\_

Contractor: \_\_\_\_\_

Engineer: \_\_\_\_\_

Approval: \_\_\_\_\_

## Standard Dual-Thread Aerators

### Design Features:

- Lead Free\* Brass Housing
- Chrome Finish
- Max Flow Rate of 2.2 GPM @ 60 psi
- Dual Thread
- 15/16" - 27T - Male
- 55/64" - 27T - Female
- Imported



\*The wetted surface of this product contacted by consumable water contains less than one quarter of a percent (.25%) of lead by weight.

Material Specifications	
Part	Material
Body	CP Brass
Flow Restrictor	Nylon
Washer	Rubber
Screen	CP Brass

**LF** Meets AB1953/NSF61G Standard  
 Meets CSA B125 Standard  
 Meets ASME A112.18.1M Standard

W-R#	Max Flow Rate at 60 PSI	Description	Single Item Weight	Aerators Sold in Bulk
4305004	2.2 GPM	Standard	.0285 lbs.	25
4305204	2.2 GPM	Slotted	.0440 lbs.	25

  

W-R#	Max Flow Rate at 60 PSI		Tube Weight	Aerators per Tube
4301005	2.2 GPM	Standard	.1755 lbs.	6
4301007	2.2 GPM	Slotted	.2685 lbs.	6

  

W-R#	Max Flow Rate at 60 PSI		Display Weight	Aerators per Display
4301001	2.2 GPM	Standard	4.56 lbs.	144
4301003	2.2 GPM	Slotted	6.70 lbs.	144