



Job Name: _____

Job Location: _____

Contractor: _____

Engineer: _____

Approval: _____

Wal-Rich Low-Pressure Gas Test Kit with Rubber Bulb

Design Features:

- Uses a 2-1/2" Diaphragm Gauge with the following Features:
 1/4" NPT Lower Connection
 Black Steel Case
 Accuracy: 1.5% of Full Scale Range

Also Includes the Following:

1. Hexagonal test block 3/4" FIP
 Brass-Plated Manifold
2. 1/8" Air Valve
3. 1/8" Male X Female Air Cock
4. Rubber Bulb with Valve and 12" Tube
5. 1/2" x 40" Teflon Tape
6. Plastic Storage Case



Use: For pressure testing of gas piping.

The key to the **W-R Low Pressure Gas Test Kit** is the diaphragm actuated gauge. Standard pressure gauges are not capable of measuring minute variations because they use a bourdon tube. This type of measuring element, which is effective for higher pressures, will not detect the minute variations in pressure when a leak exists.

W-R#	Size of Gauge	Range	Increments	Weight
GT-5	2-1/2"	0 to 5 psi	1/10 lb.	1.505 lbs.
GT-10	2-1/2"	0 to 10 psi	1/10 lb.	1.505 lbs.

Please Note: This gauge is extremely sensitive. Overpressurizing this gauge will cause the measuring element to fail and render the gauge inoperable. Wal-Rich will not accept returns of gauges that are improperly operated.

Warning: Misuse of this product may cause explosion and personal injury. Read ANSI-B40.1 and apparatus installation/operating instructions prior to use. **DO NOT USE ON OXYGEN SERVICE**