

Turn to Quality. Turn to Dahl.

| Job Name: | |
|---------------|--|
| Job Location: | |
| Contractor: | |
| Engineer: | |
| Approval: | |

Dahl Mini-Ball® Quarter-Turn Angle Stops

Design Features:

- Lead Free* Brass
- Chrome Finish
- Corrosion & Heat Resistant
- Non-Rising Stem
- Quick 1/4 Turn Shut-Off
- 25 Year Warranty
- · Made in Canada with American Materials

Operating Specifications:

Temperature: 250° F Pressure: 250 psi Max



Internal Material Specifications

| Part | Material | | | | |
|--|---------------------------------------|--|--|--|--|
| Spindle Upper O-ring Lower O-ring | Nickel Plated Brass EPDM Viton* | | | | |
| Sleve | Brass | | | | |
| Ball | Plated Brass | | | | |
| Seals | Telflon* | | | | |
| *Registered Trademark of E,I. Dupont Nemours | | | | | |

| External Material Specifications | | | | | | |
|----------------------------------|----------------|--------------------|--|--|--|--|
| No. | Part | Material | | | | |
| 1 | Handle | Nickel Plated Zinc | | | | |
| 2 | Bonnet | Brass C69300 | | | | |
| 3 | Compresion Nut | Brass C69300 | | | | |
| 4 | Body | Brass C69300 | | | | |







Meets AB1953/NSF61G Standard

| W-R# | Description | Weight | н | Min | Вох |
|---------|-------------------|-----------|--------|-----|-----|
| MB202LF | 3/8"OD x 3/8" IPS | .345 lbs. | 2-1/2" | 1 | 10 |
| MB206LF | 3/8"OD x 1/2" IPS | .388 lbs. | 2-5/8" | 1 | 10 |
| MB002LF | 3/8"OD x 1/2" SWT | .278 lbs. | 2-3/8" | 1 | 10 |
| MB102LF | 3/8"OD x 5/8"OD | .337 lbs. | 2-5/8" | 1 | 10 |

*The wetted surface of this product contacted by consumable water contains less than one tenth of a percent (.1%) of lead by weight.